

# Product Cut Sheet

## PDU/POWER STRIP LASHING BRACKET FOR F-SERIES TERAFRAME® CABINET




The PDU/Power Strip Lashing Bracket supports one or two CPI Vertical PDUs or Power Strips for Cabinets and provides multiple attachment points for fastening power cable bundles. The PDU/Power Strip Lashing Bracket attaches to the cabinet frame behind the rear equipment mounting rails.

- Supports two 2.3"W (58 mm) or narrower CPI Vertical Power Strips for Cabinets or one 3.5"W (89 mm) CPI Vertical Power Strip for Cabinets\*
- The manager is S-shaped, 8.375"W x 1.7"D (213 mm x 42 mm) and requires a minimum 5" (127 mm) equipment mounting rail setback, although the recommended setback is 8.5" (216 mm)
- Power strips attach to the front portion of the bracket using tool-less keyhole attachment points so that the outlets face the middle of the cabinet for easy access to power connections
- Keyhole attachment points are located 36.75" ( 933 mm) apart for 38.5"L (970 mm) Vertical Power Strips and 64.75" (1645 mm) apart for 66"L (1680 mm) Vertical Power Strips, 68.5"L (1740 mm) PDUs and 70.5" (1791 mm) PDUs. The 38.5"L (970 mm) Vertical Power Strip can be attached at the top, middle or bottom of the bracket; the middle set of keyholes is for a single 3.5" (89 mm) wide PDU/power strip
- The cable management area of the bracket is a recessed fin with bridge lances for securing power cable bundles with Saf-T-Grip® Cable Management Straps or cable ties; the mounting rail can be positioned over the recessed fin to allow the minimum 5" (127 mm) equipment rail setback in shallow depth cabinets
- Select the Power Strip Lashing Bracket to match the height (U) of the cabinet
- Designed for use with Gen 2 F-Series TeraFrame Cabinets only

For assistance in configuring your TeraFrame Cabinet, contact Technical Support at 800-834-4969 or visit CPI's Product Configurator at [www.chatsworth.com/configurator](http://www.chatsworth.com/configurator).

\*A 43U (-C03) Bracket is required to support 68.5"L (1740 mm) PDUs.  
A 44U (-C04) Bracket is required to support 70.5"L (1791 mm) PDUs.



PDU/Power Strip Lashing Bracket installed

Power Strip Lashing Bar		
Part Number	Description	Shipping Weight
35086-C01	For 36U Cabinet	14 lb (6.4 kg)
35086-C02	For 42U Cabinet	14 lb (6.4 kg)
35086-C03	For 43U Cabinet	15 lb (6.8 kg)
35086-C04	For 44U Cabinet	15 lb (6.8 kg)
35086-C05	For 45U Cabinet	15 lb (6.8 kg)
35086-C06	For 46U Cabinet	15 lb (6.8 kg)
35086-C07	For 47U Cabinet	16 lb (7.3 kg)
35086-C08	For 48U Cabinet	16 lb (7.3 kg)
35086-C09	For 49U Cabinet	16 lb (7.3 kg)
35086-C10	For 50U Cabinet	16 lb (7.3 kg)
35086-C11	For 51U Cabinet	17 lb (7.7 kg)

Not available for 24U Cabinets. (-C01) holds 38.5"L (970 mm) vertical power strips only. (-C03) Bracket required for 68.5"L (1740 mm) PDUs. (-C04) Bracket is required for 70.5"L (1791 mm) PDUs. Color is black.

800-834-4969 in U.S. & Canada • [www.chatsworth.com](http://www.chatsworth.com)



CHATSWORTH PRODUCTS, INC.