






Universal Cable Runway
UL Classified Cable Runway
Adjustable Cable Runway
Runway Splices, Turns & Supports
OnTrac® Shaped Wire Cable Tray
OnTrac® Splices, Turns & Supports

| | | | | | |
|---|---|--|---|--|--|
| <p>Application: Use in telecommunication rooms, equipment rooms and data centers</p> | <p>Application: Simplifies the cable runway grounding and bonding process</p> | <p>Application: Cross Members can be easily repositioned for maximum versatility in aligning cable drops</p> | <p>Application: Connect and support Cable Runway to form a continuous pathway for cables</p> | <p>Application: Use for high-density cable distribution in data centers and commercial spaces</p> | <p>Application: Connect and support OnTrac Cable Tray to form a continuous pathway for cables</p> |
| <p>Key Features:</p> <ul style="list-style-type: none"> • UL Classified for suitability as an equipment grounding conductor only • Remove paint to bond cable runway sections with splices or ground straps • 9 sizes • No side walls, 1-1/2" H (38 mm) stringers • 12" (300 mm) rung spacing | <p>Key Features:</p> <ul style="list-style-type: none"> • UL Classified for suitability as an equipment grounding conductor only • Splices bond cable runway sections; a separate bonding step is not required • 7 sizes • No side walls, 1-1/2" H (38 mm) stringers • 9" (230 mm) rung spacing | <p>Key Features:</p> <ul style="list-style-type: none"> • Supports cable and fiber from floors, ceilings, walls and tops of cabinets and racks • Combines with other CPI Runway and accessories to form a complete pathway solution • Compatible with CPI's Universal, TELCO and UL Classified Runway • Adapts to any data center or computer room • Thread-forming screws cut through paint to form an electrical bond between Stringers and Cross Members • Use Tool-less Radius Drops and Dividers to manage cable • Ships assembled or unassembled | <p>Key Features:</p> <ul style="list-style-type: none"> • Support cable runway from the ceiling, wall, floor or tops of racks and cabinets • Connect Cable Runway end-to-end with Butt Splice Kits • Create 90° L- or T-shaped intersections with Junction Splice Kits • Use E-Bends and Corner Brackets to make smooth turns • Change elevations with Radius Bends • Add Cable Retaining Posts when cables are stacked over 2" H (50 mm) • Use Radius Drop wherever cables exit the runway | <p>Key Features:</p> <ul style="list-style-type: none"> • Unique flattened cross supports provide a larger contact surface for cables, and reduce cable strain where cables cross tray wires • UL Classified for suitability as an equipment grounding conductor only • 22 sizes • Side Walls: 2" H (50 mm), 4" H (100 mm) or 6" H (150 mm) • 2" x 4" (50 mm x 100 mm) wire mesh | <p>Key Features:</p> <ul style="list-style-type: none"> • Support Shaped or Standard OnTrac Wire Cable Tray from the ceiling, wall, floor or the tops of racks and cabinets • Use above drop ceilings or below raised access floors • Cut and form to create smooth turns and changes in elevation • Use splice kits to bolt and electrically bond sections of wire mesh tray together • Support from the ceiling with Edge Hanger, Trapeze Support Bracket or Center Support Bracket • Support from the wall with C Support Bracket, Wall-Mount Angle, Triangle Support Bracket or L Support Bracket • Support from the floor with Under Floor Support, Under Floor C Bracket, Pedestal Clamp Bracket or Pedestal Clamp Bracket Kit |
| <p>Widths (9):</p> <ul style="list-style-type: none"> • 4" (100 mm) • 6" (150 mm) • 9" (230 mm) • 12" (300 mm) • 15" (380 mm) • 18" (460 mm) • 24" (610 mm) • 30" (760 mm) • 36" (910 mm) | <p>Widths (7):</p> <ul style="list-style-type: none"> • 6" (150 mm) • 9" (230 mm) • 12" (300 mm) • 15" (380 mm) • 18" (460 mm) • 20" (510 mm) • 24" (610 mm) | <p>Widths (9):</p> <ul style="list-style-type: none"> • 4" (100 mm) • 6" (150 mm) • 9" (230 mm) • 12" (300 mm) • 15" (380 mm) • 18" (460 mm) • 24" (610 mm) • 30" (760 mm) • 36" (910 mm) | <p>Construction:</p> <ul style="list-style-type: none"> • Welded or formed steel, zinc-plated or painted finish | <p>Widths (8):</p> <ul style="list-style-type: none"> • 4" (100 mm) • 6" (150 mm) • 8" (200 mm) • 12" (300 mm) • 16" (400 mm) • 18" (450 mm) • 20" (500 mm) • 24" (600 mm) | <p>Length:</p> <ul style="list-style-type: none"> • 118" (2997 mm) • 10' L (3 m) |
| <p>Length:</p> <ul style="list-style-type: none"> • 119.5" (3035 mm) • 9' - 11.5" (3 m) | <p>Length:</p> <ul style="list-style-type: none"> • 116.5" (2959 mm) • 9' - 8.5" (2.9 m) | <p>Length:</p> <ul style="list-style-type: none"> • 119.5" (3035 mm) | <p>Construction:</p> <ul style="list-style-type: none"> • Roll formed Steel Stringers • Aluminum Cross Members • Painted finish | <p>Length:</p> <ul style="list-style-type: none"> • 118" (2997 mm) • 10' L (3 m) | <p>Construction:</p> <ul style="list-style-type: none"> • Welded or formed steel, pre-galvanized, black painted or zinc plated finish |
| <p>Support Spacing:</p> <ul style="list-style-type: none"> • Every 5' (1.5 m) of span and within 2' (0.6 m) of any intersection | <p>Support Spacing:</p> <ul style="list-style-type: none"> • Every 5' (1.5 m) of span and within 2' (0.6 m) of any intersection | <p>Support Spacing:</p> <ul style="list-style-type: none"> • Every 5' (1.5 m) of span and within 2' (0.6 m) of any intersection • Maximum load is 132 lb/ft • **at recommended support spacing | <p>Construction:</p> <ul style="list-style-type: none"> • Welded steel, pre-galvanized or black painted finish | <p>Support Spacing:</p> <ul style="list-style-type: none"> • Every 6' (1.8 m) of span and within 2' (0.6 m) of any intersection | <p>Construction:</p> <ul style="list-style-type: none"> • Welded or formed steel, pre-galvanized, black painted or zinc plated finish |
| <p>Construction:</p> <ul style="list-style-type: none"> • Welded steel, painted finish | <p>Construction:</p> <ul style="list-style-type: none"> • Welded steel, zinc plated finish | <p>Construction:</p> <ul style="list-style-type: none"> • Roll formed Steel Stringers • Aluminum Cross Members • Painted finish | | | |



Universal Cable Runway

UL Classified Cable Runway

Adjustable Cable Runway

Runway Splices, Turns & Supports

OnTrac® Shaped Wire Cable Tray

OnTrac® Splices, Turns & Supports

| Part No. | Description | Wt. lb (kg) | Part No. | Description | Wt. lb (kg) | Part No. | Description | Wt. lb (kg) | Part No. | Description | Wt. lb (kg) | Part No. | Description | Wt. lb (kg) | Part No. | Description | Wt. lb (kg) |
|---|--|-------------|--|---|-------------|---|--|-------------|---|---|-------------|---|--|-------------|--|--|-------------|
| 10250-X04 | 1.5"H x 4"W x 9'-11.5"L 38 mm x 100 mm x 3 m | 18 (8.2) | 11275-X06 | 1.5"H x 6"W x 9'-8.5"L 38 mm x 150 mm x 2.9 m | 19 (8.6) | 14300-X04 | 1.5"H x 4"W x 119.5"L 38 mm x 102 mm x 3035 mm | 17 (8.0) | Triangle Support Bracket | | | 36811-X04 | 2"H x 4"W x 10'L 50 mm x 100 mm x 3 m | 11 (5.0) | 34738-501 | Standard Splice Kit, 50 Pk | 11 (5.0) |
| 10250-X06 | 1.5"H x 6"W x 9'-11.5"L 38 mm x 150 mm x 3 m | 19 (8.6) | 11275-X09 | 1.5"H x 9"W x 9'-8.5"L 38 mm x 230 mm x 2.9 m | 20 (9.1) | 14300-X06 | 1.5"H x 6"W x 119.5"L 38 mm x 152 mm x 3035 mm | 18 (8.2) | Wall Support, Side, for 12"W (300 mm) Runway | 5 (2.3) | | 36811-X06 | 2"H x 6"W x 10'L 50 mm x 150 mm x 3 m | 12 (5.4) | 34740-501 | 90° Splice Bar Kit | 2 (0.9) |
| 10250-X09 | 1.5"H x 9"W x 9'-11.5"L 38 mm x 230 mm x 3 m | 20 (9.1) | 11275-X12 | 1.5"H x 12"W x 9'-8.5"L 38 mm x 300 mm x 2.9 m | 22 (10.0) | 14300-X09 | 1.5"H x 9"W x 119.5"L 38 mm x 229 mm x 3035 mm | 19 (8.6) | Wall Support, Side, for 18"W (460 mm) Runway | 8 (3.6) | | 36811-X08 | 2"H x 8"W x 10'L 50 mm x 200 mm x 3 m | 14 (6.4) | <i>Note: Use Standard Splice Kit to make turns and end-to-end connections. Use 90° Splice Bar Kit to make (1) T-splice or (2) L-splices.</i> | | |
| 10250-X12 | 1.5"H x 12"W x 9'-11.5"L 38 mm x 300 mm x 3 m | 25 (11.3) | 11275-X15 | 1.5"H x 15"W x 9'-8.5"L 38 mm x 380 mm x 2.9 m | 26 (11.8) | 14300-X12 | 1.5"H x 12"W x 119.5"L 38 mm x 305 mm x 3035 mm | 20 (9.1) | Wall Support, Side, for 24"W (610 mm) Runway | 9 (4.1) | | 36811-X12 | 2"H x 12"W x 10'L 50 mm x 300 mm x 3 m | 17 (7.7) | | | |
| 10250-X15 | 1.5"H x 15"W x 9'-11.5"L 38 mm x 380 mm x 3 m | 27 (12.2) | 11275-X18 | 1.5"H x 18"W x 9'-8.5"L 38 mm x 460 mm x 2.9 m | 28 (12.7) | 14300-X15 | 1.5"H x 15"W x 119.5"L 38 mm x 381 mm x 3035 mm | 21 (9.8) | Wall Angle Support Kit | | | 36811-X16 | 2"H x 16"W x 10'L 50 mm x 400 mm x 3 m | 20 (9.1) | 34730-612 | Trapeze Support Brkt, 12"W (300 mm) | 2 (0.9) |
| 10250-X18 | 1.5"H x 18"W x 9'-11.5"L 38 mm x 460 mm x 3 m | 29 (13.2) | 11275-X20 | 1.5"H x 20"W x 9'-8.5"L 38 mm x 510 mm x 2.9 m | 29 (13.2) | 14300-X18 | 1.5"H x 18"W x 119.5"L 38 mm x 457 mm x 3035 mm | 22 (10.9) | Wall Support, End, for 12"W (300 mm) Runway | 3 (1.4) | | 36811-X18 | 2"H x 18"W x 10'L 50 mm x 450 mm x 3 m | 21 (9.5) | 34730-624 | Trapeze Support Brkt, 24"W (600 mm) | 3 (1.4) |
| 10250-X24 | 1.5"H x 24"W x 9'-11.5"L 38 mm x 610 mm x 3 m | 32 (14.5) | 11275-X24 | 1.5"H x 24"W x 9'-8.5"L 38 mm x 610 mm x 2.9 m | 31 (14.1) | 14300-X24 | 1.5"H x 24"W x 119.5"L 38 mm x 610 mm x 3035 mm | 25 (11.0) | Wall Support, End, for 18"W (460 mm) Runway | 5 (2.3) | | 36811-X20 | 2"H x 20"W x 10'L 50 mm x 500 mm x 3 m | 23 (10.6) | 34735-612 | Wall-Mount Angle, 12"W (300 mm) | 1 (0.5) |
| 10250-X31 | 1.5"H x 30"W x 9'-11.5"L 38 mm x 760 mm x 3 m | 35 (15.7) | <i>X=Color over Zinc: 0=Gold, 7=Black.</i> | | | 14300-X30 | 1.5"H x 30"W x 119.5"L 38 mm x 762 mm x 3035 mm | 27 (12.0) | Wall Support, End, for 24"W (610 mm) Runway | 6 (2.7) | | 36811-X24 | 2"H x 24"W x 10'L 50 mm x 600 mm x 3 m | 26 (11.8) | 34735-624 | Wall-Mount Angle, 24"W (600 mm) | 2 (0.9) |
| 10250-X37 | 1.5"H x 36"W x 9'-11.5"L 38 mm x 910 mm x 3 m | 38 (17.2) | Accessories | | | 14300-X36 | 1.5"H x 36"W x 119.5"L 38 mm x 914 mm x 3035 mm | 30 (13.0) | Center Support Kit | | | 36821-X04 | 4"H x 4"W x 10'L 100 mm x 100 mm x 3 m | 14 (6.4) | 34733-612 | Triangle Support Brkt, 12"W (300 mm) | 2 (0.9) |
| <i>Note: X=Color: 1=Gray, 2=Computer Beige, 7=Black, E=Glacier White.</i> | | | 16301-001 | Butt-Splice Kit | 1 (0.5) | <i>X=Color: 1=Gray, 2=Computer Beige, E=Glacier White, 7=Black.</i> | | | 12362-X12 | Ceiling Support, for 12"W (300 mm) Runway | 2 (0.9) | 36821-X06 | 4"H x 6"W x 10'L 100 mm x 150 mm x 3 m | 16 (7.3) | 34733-624 | Triangle Support Brkt, 24"W (600 mm) | 4 (1.8) |
| Accessories | | | 16302-001 | Junction-Splice Kit | 1 (0.5) | Accessories | | | 12362-X18 | Ceiling Support, for 18"W (460 mm) Runway | 4 (1.8) | 36821-X08 | 4"H x 8"W x 10'L 100 mm x 200 mm x 3 m | 18 (8.7) | 34737-502 | Pedestal Clamp Brkt Kit, 2' (0.6 m) Floor | 4 (1.8) |
| <i>Note: X=Color: 1=Gray, 2=Computer Beige, 7=Black, E=Glacier White.</i> | | | 11959-015 | Corner Bracket, 15"W (380 mm) | 4 (1.8) | <i>X=Color: 1=Gray, 2=Computer Beige, E=Glacier White, 7=Black.</i> | | | 12362-X24 | Ceiling Support, for 24"W (610 mm) Runway | 5 (2.3) | 36821-X12 | 4"H x 12"W x 10'L 100 mm x 300 mm x 3 m | 21 (8.5) | <i>Note: Install Trapeze Support Bracket with 3/8" (M10) threaded rod and hardware. Attach Wall-Mount Angle with 1/4" (M6) hardware. Attach Triangle Support Bracket with 3/8" (M10) hardware. Pedestal Clamp Support Kit attaches to 1" - 2" round pedestals.</i> | | |
| Accessories | | | 10822-012 | E-Bend, 12"W (300 mm) | 12 (5.4) | Accessories | | | 3" Channel Rack-To-Runway Mounting Plate | | | 36821-X16 | 4"H x 16"W x 10'L 100 mm x 400 mm x 3 m | 24 (10.9) | | | |
| Part No. | | | 10723-012 | Outside Radius Bend, 12"W (300 mm) | 4 (1.8) | Part No. | | | 10595-X12 | Rack-Top Support, for 12"W (300 mm) Runway | 5 (2.3) | 36821-X18 | 4"H x 18"W x 10'L 100 mm x 450 mm x 3 m | 25 (11.3) | Accessories | | |
| Description | | | 10724-012 | Inside Radius Bend, 12"W (300 mm) | 4 (1.8) | Description | | | 10595-X18 | Rack-Top Support, for 18"W (460 mm) Runway | 7 (3.2) | 36821-X20 | 4"H x 20"W x 10'L 100 mm x 500 mm x 3 m | 27 (12.2) | Part No. | | |
| Wt. lb (kg) | | | 10596-058 | Cable Retaining Post, 8"H (200 mm), Pack of 50 | 33 (15.0) | Wt. lb (kg) | | | 12408-X24 | Rack-Top Support, for 24"W (610 mm) Runway | 4 (1.8) | 36821-X24 | 4"H x 24"W x 10'L 100 mm x 600 mm x 3 m | 30 (13.6) | Description | | |
| | | | 13392-712 | Cable Runway Dividers Pack of 25, Black | 3 (1.4) | | | | <i>(-024) not available. Use with CPI Standard and Universal Racks.</i> | | | 36831-X08 | 6"H x 8"W x 10'L 150 mm x 200 mm x 3 m | 22 (10.0) | Wt. lb (kg) | | |
| | | | 13395-704 | Patch Rack, 4U x 19"W w/ Side Stringer Brackets | 5 (2.3) | | | | Elevation Kit for 2-Post Racks | | | 36831-X08 | 6"H x 8"W x 10'L 150 mm x 200 mm x 3 m | 22 (10.0) | 34741-501 | | |
| | | | <i>Note: X=Color: 1=Gray, 2=Computer Beige, 7=Black, E=Glacier White.</i> | | | | | | | | | 36831-X12 | 6"H x 12"W x 10'L 150 mm x 300 mm x 3 m | 25 (11.3) | Tool-less Radius Drop, 7.75"W (197 mm) | | |
| | | | <i>*All Runway widths available for this part number. Contact Tech Support at 800-834-4969 for assistance specifying splices and supports.</i> | | | | | | | | | 36831-X16 | 6"H x 16"W x 10'L 150 mm x 400 mm x 3 m | 28 (12.7) | 34838-001 | | |
| | | | | | | | | | | | | 36831-X18 | 6"H x 18"W x 10'L 150 mm x 450 mm x 3 m | 29 (13.2) | Split Bolt Grounding Clamp, 1 (0.5) 10 Pack | | |
| | | | | | | | | | | | | 36831-X20 | 6"H x 20"W x 10'L 150 mm x 500 mm x 3 m | 31 (14.1) | 34749-001 | | |
| | | | | | | | | | | | | 36831-X24 | 6"H x 24"W x 10'L 150 mm x 600 mm x 3 m | 34 (15.4) | Label Holder, 10 Pack | | |
| | | | | | | | | | | | | <i>Note: X=Color: 6=Pre-Galvanized, 7=Black, E=Glacier White.</i> | | | 34839-001 | | |
| | | | | | | | | | | | | <i>4"W (100 mm) not UL Classified.</i> | | | Cable Tray Cutting Tool | | |
| | | | | | | | | | | | | | | | <i>Note: Other supports are available.</i> | | |
| | | | | | | | | | | | | | | | <i>Contact Tech Support at 800-834-4969 for assistance specifying splices and supports.</i> | | |

