


NEW CATALOG ITEM

ORGANIZING. STORING. SECURING.



FEATURES:

- The MegaFrame Seismic Equipment Bracket secures shelf-mount equipment by bracing the equipment directly to the cabinet's mounting rails which helps prevent equipment movement during seismic events or when cabinets are moved on casters
- The bracket easily adjusts into multiple configurations which provides security for shelf-mount equipment of different depth or height
- The bracket is available in both 19" and 23" rack-mount widths and will adjust in depth for use in any of CPI's 24", 30", 36", or 39" deep MegaFrame Cabinets

An Employee Owned Corporation



CHATSWORTH PRODUCTS, INC.

Chatsworth, CA Operations
818-882-8595 • 818-718-0473 FAX
Georgetown, TX Operations
512-863-7800 • 512-869-1374 FAX
New Bern, NC Operations
252-514-2779 • 252-514-2977 FAX
New Castle, IN Operations
765-599-9000 • 765-593-0950 FAX
Email
techsupport@chatsworth.com
Web site
www.chatsworth.com

MEGAFRAME® SEISMIC EQUIPMENT BRACKET

In areas of seismic activity or whenever casters are used on a MegaFrame® Cabinet, shelf-mounted equipment has the potential to be damaged by bumping or shifting off of the shelf. The new CPI MegaFrame Seismic Equipment Bracket was designed to help prevent this type of damage.

The Seismic Equipment Bracket prevents back-and-forth, side-to-side, and up-and-down movement of shelf-mount equipment by bracing the equipment's chassis to the MegaFrame's vertical mounting rails. The Seismic Equipment Bracket can adjust in depth and width to secure one or two pieces of equipment to a MegaFrame Fixed Shelf. Three configurations are possible with the Seismic Bracket: 1) Secure a single piece of equipment, 2) Secure two pieces of equipment of the same height, or 3) Secure two pieces of equipment of the same depth.

The brackets are available for both 19" and 23" MegaFrame Cabinets. Both brackets use only 1 RMU (1.75") of mounting space. The 19" bracket will secure a single piece of equipment up to 16" in width or two pieces of equipment totaling 15" in width. The 23" bracket will secure a single piece of equipment up to 20" in width or two pieces of equipment totaling 19" in width. Both brackets can secure equipment between 15" and 32" in depth. The bracket's mounting flanges will adjust to match the existing depth of the cabinet's vertical mounting rails anywhere from 22" to 39" deep. Thus, the bracket can be added to any of CPI's 24", 30", 36", or 39" deep MegaFrame Cabinets. The brackets are available in three standard finishes: gray, computer white, and black. Protect your investment today! Simply select brackets to match the width and finish of your existing cabinets.

Please contact your authorized CPI Distributor or CPI Customer Service Representative for more information, or go to www.chatsworth.com.

MegaFrame Seismic Brackets			
19" Width	23" Width	Finish	Shipping Weight
14061-119	14061-123	Gray	6 LB
14061-219	14061-223	White	6 LB
14061-719	14061-723	Black	6 LB

