




CHATSWORTH
PRODUCTS

Aluminum-to-Aluminum or Aluminum-to-Copper Antioxidant Joint Compound

Recommended for all aluminum-to-aluminum and aluminum-to-copper connectors, bare conductors, Busbars, insulated conductors and conduit threads.

- Oxide-inhibiting joint compound is used to improve the electrical conductivity and enhance the integrity of any grounding or bonding connection
- Good for all voltages
- Assures a high-connectivity joint by sealing out air and moisture to prevent corrosion and reformation of oxide film
- Also used as an anti-seizing thread lubricant and ensures continuity of ground on aluminum conduit threads
- Bulk packaging quantities available



ORDERING INFORMATION

Part Number	Description	Shipping Weight lb (kg)
40166-101	Antioxidant, Gray, .5 oz, 1 unit	1 (0.5)
40166-801	Antioxidant, Gray, 8 oz, 1 unit	1 (0.5)
40166-150	Antioxidant, Gray, .5 oz, 50	2 (0.9)
40166-812	Antioxidant, Gray, 8 oz, 12	2 (0.9)

United States & Canada
 Simi Valley, CA
 800-834-4969
 Toronto, Ontario, Canada
 +905-850-7770
 chatsworth.com
 techsupport@chatsworth.com

Latin America
 Mexico City, Mexico
 +52-55-5203-7525
 Toll Free within Mexico
 800-201-7592
 chatsworth.com.co

Europe
 Buckinghamshire
 England, UK
 +44-1628-524-834

Middle East & Africa
 Dubai, UAE
 +971-4-2602125

Asia Pacific
 Jing'an District,
 Shanghai, China
 +86 21 6880-0266
 chatsworth.com.cn