






Universal Cable Runway	UL Classified Cable Runway	Adjustable Cable Runway	Supports for Cable Runway	Pemsma® Rejiband® Wire Mesh Cable Tray	Accessories for Pemsma® Rejiband® Wire Mesh Cable Tray
------------------------	----------------------------	-------------------------	---------------------------	--	--

<p>Application: Use in telecommunication rooms, equipment rooms and data centers</p> <p>Key Features:</p> <ul style="list-style-type: none"> • UL Classified for suitability as an equipment grounding conductor only* • Remove paint to bond cable runway sections with splices or ground straps. • 9 widths • 1-1/2" H (38 mm) stringers • 12" (300 mm) cross member spacing • Powder-coated finish <p><i>*Remove paint to bond cable runway sections with splices or ground straps</i></p> <p>Widths (9):</p> <ul style="list-style-type: none"> • 4" (100 mm) • 6" (150 mm) • 9" (230 mm) • 12" (300 mm) • 15" (380 mm) • 18" (460 mm) • 24" (610 mm) • 30" (760 mm) • 36" (910 mm) <p>Length:</p> <ul style="list-style-type: none"> • 119.5" (3035 mm) <p>Support Spacing:</p> <ul style="list-style-type: none"> • Load rating is 132 lb/ft with a support span of 5' (1.5 m) <p>Construction:</p> <ul style="list-style-type: none"> • Welded steel, painted finish 	<p>Application: Simplifies the cable runway grounding and bonding process</p> <p>Key Features:</p> <ul style="list-style-type: none"> • UL Classified for suitability as an equipment grounding conductor only • Electrical bond is achieved via Splice Kits; a separate bonding step is not required, saving on installation time. • 7 sizes • 9" (230 mm) cross member spacing • Zinc-plated finish <p>Widths (7):</p> <ul style="list-style-type: none"> • 6" (150 mm) • 12" (300 mm) • 15" (380 mm) • 18" (460 mm) • 20" (510 mm) • 24" (610 mm) <p>Length:</p> <ul style="list-style-type: none"> • 116.5" (2959 mm) <p>Support Spacing:</p> <ul style="list-style-type: none"> • Load rating is 132 lb/ft with a support span of 5' (1.5 m) <p>Construction:</p> <ul style="list-style-type: none"> • Welded steel, zinc plated finish 	<p>Application: Cross Members can be easily repositioned for maximum versatility in aligning cable drops</p> <p>Key Features:</p> <ul style="list-style-type: none"> • UL Classified for suitability as an equipment grounding conductor only • Supports cable and fiber from floors, ceilings, walls and tops of cabinets and racks • Use in conjunction with other CPI Runway and accessories to form a complete pathway solution • Adapts to any data center or computer room • Ships assembled or unassembled • Powder-coated finish <p>Widths (9):</p> <ul style="list-style-type: none"> • 4" (100 mm) • 6" (150 mm) • 9" (230 mm) • 12" (300 mm) • 15" (380 mm) • 18" (460 mm) • 24" (610 mm) • 30" (760 mm) • 36" (910 mm) <p>Length:</p> <ul style="list-style-type: none"> • 119.5" (3035 mm) <p>Support Spacing:</p> <ul style="list-style-type: none"> • Load rating is 132 lb/ft with a support span of 5' (1.5 m) <p>Construction:</p> <ul style="list-style-type: none"> • Roll-formed Steel Stringers • Aluminum Cross Members • Painted finish 	<p>Application: Connect and support Cable Runway to form a continuous pathway for cables</p> <p>Key Features:</p> <ul style="list-style-type: none"> • Support cable runway from the ceiling, wall, floor or tops of racks and cabinets • Connect Cable Runway end-to-end with Butt Splice Kits • Create 90° L- or T-shaped intersections with Junction Splice Kits • Use E-Bends and Corner Brackets to make smooth turns • Change elevations with Radius Bends • Add Cable Retaining Posts when cables are stacked over 2" H (50 mm) • Tool-less Radius Drops and Cross Members can be repositioned anywhere along the runway for maximum versatility in aligning cable drops. <p>Construction:</p> <ul style="list-style-type: none"> • Welded or formed steel, zinc-plated or painted finish 	<p>Application: Use for high-density cable distribution in data centers and commercial spaces</p> <p>Key Features:</p> <ul style="list-style-type: none"> • UL Certified • Tray can be cut and formed into turns and transitions using standard splices • Zinc Electroplate and BLACK C8® finish options • Both finishes allow bonding through splice connections for electrical continuity. • The tops of trays are rounded and smooth to protect installers and cables from cuts • The BLACK C8 finish option meets resistance class IEC 61537 Class C8, delivering corrosion resistance almost equivalent to stainless steel. <p>Widths (8):</p> <ul style="list-style-type: none"> • 4" (100 mm) • 6" (150 mm) • 8" (200 mm) • 12" (300 mm) • 18" (450 mm) • 24" (600 mm) <p>Length:</p> <ul style="list-style-type: none"> • 118.1" (3 m) <p>Support Spacing:</p> <ul style="list-style-type: none"> • Load rating varies with tray size. The recommended support span is 5' (1.5 m) <p>Construction:</p> <ul style="list-style-type: none"> • Welded steel, zinc electroplate or BLACK C8 	<p>Application: Connect and support Pemsma Rejiband Wire Mesh Cable Tray to form a continuous pathway for cables</p> <p>Key Features:</p> <ul style="list-style-type: none"> • Support Pemsma Rejiband Wire Mesh Cable Tray from the ceiling, wall, floor or the tops of CPI racks and cabinets • Use above drop ceilings or below raised access floors • Many accessories require little to no tools to install, saving time and reducing labor costs • Use splice kits to attach and electrically bond sections of wire mesh tray together • Use cable management accessories to organize and protect cables <p>Construction:</p> <ul style="list-style-type: none"> • Welded or formed steel; zinc electroplate, BLACK C8 or pregalvanized
---	--	---	---	--	--



Universal Cable Runway

UL Classified Cable Runway

Adjustable Cable Runway

Supports for Cable Runway

Pemsra® Rejiband® Wire Mesh Cable Tray

Accessories for Pemsra® Rejiband® Wire Mesh Cable Tray

Part No.	Description	Wt. lb (kg)
10250-X04	1.5" H x 4" W x 9'-11.5" L 38 mm x 100 mm x 3 m	18 (8.2)
10250-X06	1.5" H x 6" W x 9'-11.5" L 38 mm x 150 mm x 3 m	19 (8.6)
10250-X09	1.5" H x 9" W x 9'-11.5" L 38 mm x 230 mm x 3 m	20 (9.1)
10250-X12	1.5" H x 12" W x 9'-11.5" L 38 mm x 300 mm x 3 m	25 (11.3)
10250-X15	1.5" H x 15" W x 9'-11.5" L 38 mm x 380 mm x 3 m	27 (12.2)
10250-X18	1.5" H x 18" W x 9'-11.5" L 38 mm x 460 mm x 3 m	29 (13.2)
10250-X24	1.5" H x 24" W x 9'-11.5" L 38 mm x 610 mm x 3 m	32 (14.5)
10250-X31	1.5" H x 30" W x 9'-11.5" L 38 mm x 760 mm x 3 m	35 (15.7)
10250-X37	1.5" H x 36" W x 9'-11.5" L 38 mm x 910 mm x 3 m	38 (17.2)
<i>Note: X=Color: 1=Gray, 2=Computer Beige, 7=Black, E=Glacier White.</i>		
Key Accessories		
Part No.	Description	Wt. lb (kg)
11301-001	Butt-Splice Kit	1 (0.5)
11302-001	Junction-Splice Kit	1 (0.5)
40164-025	Ground Strap Kit Pack of 25	12 (5.0)
11959-X15*	Corner Bracket, 15" W (380 mm)	4 (1.8)
10822-X12*	E-Bend, 12" W (300 mm)	12 (5.4)
10596-X56*	Cable Retaining Post, 6" H (150 mm), Pack of 50	33 (15.0)
10642-001	Protective End Caps	1 (0.5)
25400-X00	Touch-Up Paint, Spray Can, 12 oz (340)	2 (0.9)
13395-X04*	Patch Rack, 4U x 19" W w/Side Stringer Brackets	5 (2.3)
<i>Note: X=Color: 1=Gray, 2=Computer Beige, 7=Black, E=Glacier White. *Additional sizes available.</i>		
<i>Note: X=Color: 1=Gray, 2=Computer Beige, 7=Black, E=Glacier White. *Additional sizes available.</i>		

Part No.	Description	Wt. lb (kg)
11275-X06	1.5" H x 6" W x 9'-8.5" L 38 mm x 150 mm x 2.9 m	19 (8.6)
11275-X09	1.5" H x 9" W x 9'-8.5" L 38 mm x 230 mm x 2.9 m	20 (9.1)
11275-X12	1.5" H x 12" W x 9'-8.5" L 38 mm x 300 mm x 2.9 m	22 (10.0)
11275-X15	1.5" H x 15" W x 9'-8.5" L 38 mm x 380 mm x 2.9 m	26 (11.8)
11275-X18	1.5" H x 18" W x 9'-8.5" L 38 mm x 460 mm x 2.9 m	28 (12.7)
11275-X20	1.5" H x 20" W x 9'-8.5" L 38 mm x 510 mm x 2.9 m	29 (13.2)
11275-X24	1.5" H x 24" W x 9'-8.5" L 38 mm x 610 mm x 2.9 m	31 (14.1)
<i>X=Color over Zinc: 0=Gold, 7=Black.</i>		
Key Accessories		
Part No.	Description	Wt. lb (kg)
16301-001	Butt-Splice Kit	1 (0.5)
16302-001	Junction-Splice Kit	1 (0.5)
11959-X15*	Corner Bracket, 15" W (380 mm)	4 (1.8)
10822-X12*	E-Bend, 12" W (300 mm)	12 (5.4)
10723-X12*	Outside Radius Bend, 12" W (300 mm)	4 (1.8)
10724-X12*	Inside Radius Bend, 12" W (300 mm)	4 (1.8)
10596-X58*	Cable Retaining Post, 8" H (200 mm), Pack of 50	33 (15.0)
13395-X04*	Patch Rack, 4U x 19" W w/Side Stringer Brackets	5 (2.3)
<i>Note: X=Color: 1=Gray, 2=Computer Beige, 7=Black, E=Glacier White. *Additional sizes available.</i>		

Part No.	Description	Wt. lb (kg)
14300-X04	1.5" H x 4" W x 119.5" L 38 mm x 102 mm x 3035 mm	17 (8.0)
14300-X06	1.5" H x 6" W x 119.5" L 38 mm x 152 mm x 3035 mm	18 (8.2)
14300-X09	1.5" H x 9" W x 119.5" L 38 mm x 229 mm x 3035 mm	19 (8.6)
14300-X12	1.5" H x 12" W x 119.5" L 38 mm x 305 mm x 3035 mm	20 (9.1)
14300-X15	1.5" H x 15" W x 119.5" L 38 mm x 381 mm x 3035 mm	21 (9.8)
14300-X18	1.5" H x 18" W x 119.5" L 38 mm x 457 mm x 3035 mm	22 (10.9)
14300-X24	1.5" H x 24" W x 119.5" L 38 mm x 610 mm x 3035 mm	25 (11.0)
14300-X30	1.5" H x 30" W x 119.5" L 38 mm x 762 mm x 3035 mm	27 (12.0)
14300-X36	1.5" H x 36" W x 119.5" L 38 mm x 914 mm x 3035 mm	30 (13.0)
<i>X=Color: 1=Gray, 2=Computer Beige, E=Glacier White, 7=Black.</i>		
Key Accessories		
Part No.	Description	Wt. lb (kg)
14308-001	Tool-less Pathway Divider Pack of 10	2 (1.0)
14304-X12*	Tool-less Cross Member Radius Drop, 12" W (300 mm)	2 (1.0)
14305-X00	Tool-less Stringer Radius Drop, Large	3 (1.0)
14305-X01	Tool-less Stringer Radius Drop, Small	2 (1.0)
14302-X12*	Cross Member Kit, 12" W (300 mm)	4 (2.0)
14303-X10	Stringer Kit, 1.5" H x 0.4" W x 119.5" L 38 mm x 10 mm x 2025 mm	69 (31)
<i>Note: X=Color: 1=Gray, 2=Computer Beige, 7=Black, E=Glacier White. *Additional sizes available.</i>		
<i>Contact Tech Support at 800-834-4969 for assistance specifying splices and supports.</i>		

Part No.	Description	Wt. lb (kg)
Triangle Support Bracket		
11746-X12	Wall Support, Side, for 12" W (300 mm) Runway	5 (2.3)
11746-X18	Wall Support, Side, for 18" W (460 mm) Runway	8 (3.6)
11746-X24	Wall Support, Side, for 24" W (610 mm) Runway	9 (4.1)
Wall Angle Support Kit		
11421-X12	Wall Support, End, for 12" W (300 mm) Runway	3 (1.4)
11421-X18	Wall Support, End, for 18" W (460 mm) Runway	5 (2.3)
11421-X24	Wall Support, End, for 24" W (610 mm) Runway	6 (2.7)
Center Support Kit		
12362-X12	Ceiling Support, for 12" W (300 mm) Runway	2 (0.9)
12362-X18	Ceiling Support, for 18" W (460 mm) Runway	4 (1.8)
12362-X24	Ceiling Support, for 24" W (610 mm) Runway	5 (2.3)
3" Channel Rack-To-Runway Mounting Plate		
10595-X12	Rack-Top Support, for 12" W (300 mm) Runway	5 (2.3)
10595-X18	Rack-Top Support, for 18" W (460 mm) Runway	7 (3.2)
12408-X24*	Rack-Top Support, for 24" W (610 mm) Runway	4 (1.8)
<i>Additional sizes available. Use with CPI Standard and Universal Racks.</i>		
Elevation Kit for 2-Post Racks		
10506-X02	Elevates Runway, 2" H (50 mm), 2.5" H (64 mm) or 3" H (80 mm)	2 (0.9)
10506-X06	Elevates Runway, 4" H (100 mm), 5" H (130 mm) or 6" H (150 mm)	5 (2.3)
<i>Use with Rack-To-Runway Mounting Plate.</i>		
<i>Note: X=Color: 0=Gold, 1=Gray, 2=Computer Beige, 7=Black, E=Glacier White. *12408-024 not available Contact Tech Support at 800-834-4969 for assistance specifying splices and supports.</i>		

Part No.	Description	Wt. lb (kg)
602X2100-003	2" H x 4" W x 10' L 60 mm x 100 mm x 3 m	6 (2.7)
602X2150-003	2" H x 6" W x 10' L 60 mm x 150 mm x 3 m	7 (3.2)
602X2200-003	2" H x 8" W x 10' L 60 mm x 200 mm x 3 m	9 (4.0)
602X2300-003	2" H x 12" W x 10' L 60 mm x 300 mm x 3 m	14 (6.4)
602X2450-003	2" H x 18" W x 10' L 60 mm x 450 mm x 3 m	18 (8.2)
602X2600-003	2" H x 24" W x 10' L 60 mm x 600 mm x 3 m	23 (10.4)
602X3100-003	4" H x 4" W x 10' L 100 mm x 100 mm x 3 m	9 (4.0)
602X3150-003	4" H x 6" W x 10' L 100 mm x 150 mm x 3 m	10 (4.5)
602X3200-003	4" H x 8" W x 10' L 100 mm x 200 mm x 3 m	14 (6.4)
3602X3300-003	4" H x 12" W x 10' L 100 mm x 300 mm x 3 m	17 (7.7)
602X3450-003	4" H x 18" W x 10' L 100 mm x 450 mm x 3 m	22 (10.0)
602X3600-003	4" H x 24" W x 10' L 100 mm x 600 mm x 3 m	26 (11.7)
<i>Note: X=Finish: 1=Zinc Electroplate, 8=BLACK C8</i>		

Part No.	Description	Wt. lb (kg)
640X0061-050	Reinforced Joint Clamp Pack of 50	4 (1.8)
640X0060-050	Part Clamp Pack of 50	3 (1.3)
640X0020-025	Click Connector Pack of 25	5 (2.2)
670X0046-020	Central Hanging Plate Pack of 20	5 (2.2)
670X0070-018	Edge Hanger Pack of 18	5 (2.2)
630X2304-010	Omega SPLUS Channel 12" W (300 mm); Pack of 10	8 (3.6)
620X1304-005	Omega SPLUS Bracket 12" W (300 mm); Pack of 10	7 (3.1)
60501-X12	Wall Angle Support Kit 12" W (300 mm), Each	2.3 (1.0)
60506-X06	Elevation Kit, Each 4"-6" H (100 mm-150 mm)	3.5 (1.6)
60500-X01	Radius Drop 5.75" W (146 mm)	1.7 (0.8)
620X6010-010	Mini Universal Bracket Pack of 10	3 (1.3)
67020139-010	Data Outlet Radius Drop Black Plastic; Pack of 10	1 (0.4)
68000110-020	Cable Tie Clip Black Plastic; Pack of 20	1 (0.4)
68000058-001	Cutting Tool, Each	4 (1.8)
68000032-020	Grounding Connector Pack of 20	2 (0.9)
<i>X=Finish; 1=Zinc Electroplate, 2=Pre-Galvanized, 8=BLACK C8, E=Glacier White Powder Coat, 5=Zinc color, 7=Black powder coat</i>		
<i>Note: Not every product is available in all finishes. Some accessories are available in powder coat only.</i>		